

TOD-10201BMA-B

Dual Digit Display LED

Part Number	Chip		Face Color	Segment Color
	Material	Source Color		
TOD-10201BMA-B	AlGaInP	Ultra-Amber	Black	White


Features

- (1.0") 25.40mm digit height
- Common anode
- I.C. compatible
- Low power requirement
- RoHS compliant

Applications

- Audio equipment
- Instrument panels
- Digital read out display

Package Dimensions & Internal Circuit Diagram



Notes: 1. All dimensions are in millimeters, tolerance: ± 0.25 ; Angle: $\pm 0.1^\circ$ unless otherwise noted.
 2. Specifications are subject to change without notice.

Absolute Maximum Rating @ Ta=25°C

Parameter	Maximum Rating	Unit
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	80	mA
Power Dissipation(Except DP)	150	mW
Continuous Forward Current	20	mA
Recommend Operating Current	12	mA
Reverse Voltage(Except DP)	10	V
Operating Temperature Range	-25°C to +85°C	
Storage Temperature Range	-30°C to +85°C	
Lead-Free Solder Temperature(1/16 Inch Below Seating Plane)	260°C for 3 Sec	

Electrical / Optical Characteristic @ Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Dominant Wavelength	λ_d		605		nm	I _F =20mA
Spectral Line Half-Width	$\Delta\lambda$		18		nm	I _F =20mA
Forward Voltage(Except DP)	V _F	3.6	4.0	4.6	V	I _F =20mA
Reverse Current	I _R			100	μA	V _R =10V
Luminous Intensity Matching Rate	Iv-m			2.0:1		I _F =20mA

The DISPLAYS should be kept at 30°C or less and 60%RH or less. The DISPLAYS should be used within one year.